



AWWA C207 Table 2 Class B Ring (86 psi)

Nominal Size	OD	ID	Thickness		Drilling		Weight lbs.
			Slip-On	No. of Holes	Dia. Bolt Holes	Dia. Bolt Circle	
4	9.00	4.57	0.625	8	0.750	7.50	8
5	10.00	5.66	0.625	8	0.875	8.50	9
6	11.00	6.72	0.688	8	0.875	9.50	11
8	13.50	8.72	0.688	8	0.875	11.75	15
10	16.00	10.88	0.688	12	1.000	14.25	19
12	19.00	12.88	0.688	12	1.000	17.00	28
14	21.00	14.19	0.688	12	1.125	18.75	34
16	23.50	16.19	0.688	16	1.125	21.25	41
18	25.00	18.19	0.688	16	1.250	22.75	41
20	27.50	20.19	0.688	20	1.250	25.00	49
22	29.50	22.19	0.750	20	1.375	27.25	57
24	32.00	24.19	0.750	20	1.375	29.50	67
26	34.25	26.19	0.812	24	1.375	31.75	80
28	36.50	28.19	0.875	28	1.375	34.00	94
30	38.75	30.19	0.875	28	1.375	36.00	105
32	41.75	32.19	0.938	28	1.625	38.50	132
34	43.75	34.19	0.938	32	1.625	40.50	137
36	46.00	36.19	1.000	32	1.625	42.75	161
38	48.75	38.19	1.000	32	1.625	45.25	185
40	50.75	40.19	1.000	36	1.625	47.25	193
42	53.00	42.19	1.125	36	1.625	49.50	234
44	55.25	44.19	1.125	40	1.625	51.75	249
46	57.25	46.19	1.125	40	1.625	53.75	260
48	59.50	48.19	1.250	44	1.625	56.00	306
50	61.75	50.19	1.250	44	1.875	58.25	317
52	64.00	52.19	1.250	44	1.875	60.50	339
54	66.25	54.19	1.375	44	1.875	62.75	397
60	73.00	60.19	1.500	52	1.875	69.25	508
66	80.00	66.19	1.625	52	1.875	76.00	664
72	86.50	72.19	1.750	60	1.875	82.50	802
78	93.00	78.19	2.000	64	2.125	89.00	1000
84	99.75	84.19	2.000	64	2.125	95.50	1145
90	106.50	90.19	2.250	68	2.438	102.00	1404
96	113.25	96.19	2.250	68	2.438	108.50	1586
102	120.00	102.19	2.500	72	2.688	114.50	1912
108	126.75	108.19	2.500	72	2.688	120.75	2136
114	133.50	114.19	2.750	76	2.938	126.75	2525
120	140.25	120.19	2.750	76	2.938	132.75	2795
126	147.00	126.19	3.000	80	3.188	139.25	3252
132	153.75	132.19	3.000	80	3.188	145.75	3572
138	160.50	138.19	3.250	84	3.438	152.00	4101
144	167.25	144.19	3.250	84	3.438	158.25	4475